



LPD FM TRANSCEIVER

IC-4088E

Simplicity, Quality and Reliability You Can Count on!

- 69 channels and 38 group codes
- Diversified range of use from family recreation to light commercial use
- Splash resistant construction, equivalent to JIS Grade 4 for outdoor use
- Enhanced conversation privacy with built-in voice scrambler
- Economical 3 alkaline cells can be used, with an ultra long 65 hours use possible
- 'Smart-ring' and 'Call-ring', plus Time-out-timer function
- Compact body and reliable communication range
- External DC power jack for charging



Icom Inc.

SPECIFICATIONS

- Number of channels : 69 (simplex;
433.075–434.775MHz)
- Mode : FM (F3E)
- Frequency stability : ±2.5kHz, ±5.7ppm
- Frequency resolution : 25kHz
- Battery requirements : 3 × AA (R6) alkaline cells ;
or optional BP-202
- External power supply : 6.0V DC ±5%
(with BC-149D, CP-18E)
- Current drain (at 4.5V DC) : Less than 140mA
- Operating Temp. range : -10°C to +55°C
- Number of CTCSS freq. : 38 (67.0–250.3Hz)
- Weight (approx.) : 200g
(includes 3 alkaline cells)
- Output power : 10mW
- External MIC connector : 3-conductor 2.5 (d) mm/
2.2kΩ
- Sensitivity (12dB SINAD) : Less than 0.2µV; -14dBµV
- Audio output power : More than 100mW at 10%
distortion with an 8Ω load
- External SP connector : 3-conductor 3.5 (d) mm/
8Ω

• Battery life (Tx:Rx:Standby=1:1:8) :

Battery type	Battery life
3 alkaline cells	approx. 65 hrs.
Optional BP-202	approx. 20 hrs.

• Communication range* : Up to 2km (approx.)
(Wide, open space)


* Communication range may differ depending on weather conditions, etc.

Applicable U.S. Military Specifications

Icom makes rugged products that have been tested to and passed the following MIL-STD requirements and strict environmental standards.

Standard	MIL 810 C		MIL 810 D		MIL 810 E		MIL 810 F	
	Method	Proc.	Method	Proc.	Method	Proc.	Method	Proc.
Low Pressure	500.1	I	500.2	I, II	500.3	I, II	500.4	I, II
High Temp.	501.1	I	501.2	I, II	501.3	I, II	501.4	I, II
Low Temp.	502.1	I	502.2	I, II	502.3	I, II	502.4	I, II
Temp. Shock	503.1	I	503.2	I	503.3	I	503.4	I
Solar Radiation	505.1	I	505.2	I	505.3	I	505.4	I
Rain	506.1	I, II	506.2	I, II	506.3	I, II	506.4	I, II
Humidity	507.1	I, II	507.2	II, III	507.3	II, III	507.4	-
Salt Fog	509.1	I	509.2	I	509.3	I	509.4	-
Dust	510.1	I	510.2	I	510.3	I	510.4	I
Vibration	514.2	VIII, X	514.3	I	514.4	I	514.5	I
Shock	516.2	I, II, V	516.3	I, IV	516.4	I, IV	516.5	I, IV

DIMENSIONS



All stated specifications are subject to change without notice or obligation.

* Simple licence is required in some countries. Voice scrambler not available in some countries.

OPTIONS

BP-202 Ni-Cd BATTERY CELL ASSEMBLY



Install into the battery cell space in the transceiver.

3.6V/700mAh

BC-149D WALL CHARGER



6V DC, 1A output AC adapter. Charges the BP-202, while operating the radio.

CP-18E CIGARETTE LIGHTER CABLE



6V DC, 2A output from 12V cigarette lighter socket with internal DC-DC converter.

BC-119N DESKTOP CHARGER + BC-145E/UK AC ADAPTER + AD-105 CHARGER ADAPTER



Rapidly charges installed Ni-Cd battery cell assembly, BP-202. The charger adapter and the AC adapter supplied with the BC-119N depending on version. Charging time: 75 to 85 min.

SPEAKER-MICROPHONES



- HM-46** : Compact and lightweight. Equipped with an earphone jack.
- HM-75A** : Allows you to remotely select operating channels, etc.
- HM-131** : Durable body. Equipped with an earphone jack and revolving clip.
- HM-166** : Light weight and compact earphone-microphone with PTT switch that clips to your lapel.

HEADSETS



- HS-85** : For hands-free operation. Includes VOX, PTT and "one-touch" PTT with a time-out timer.
- VS-1** : PTT/VOX unit. Required when using the HS-94, HS-95 and HS-97 with the transceiver.
- HS-94** : Earhook headset with flexible boom microphone.
- HS-95** : Behind-the-head headset with flexible boom microphone.
- HS-97** : Throat microphone fits around your neck and picks up speech vibration.

Icom Inc.

1-1-32, Kami-minami, Hirano-ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013

URL: <http://www.icom.co.jp/world/index.html>

Count on us!

Icom America Inc.

2380 116th Avenue NE,
Bellevue, WA 98004, U.S.A.
Phone : +1 (425) 454-8155
Fax : +1 (425) 454-1509
E-mail : sales@icomamerica.com
URL : <http://www.icomamerica.com>

Icom New Zealand

146A Harris Road, East Tamaki,
Auckland, New Zealand
Phone : +64 (09) 274 4062
Fax : +64 (09) 274 4708
E-mail : inquiries@icom.co.nz
URL : <http://www.icom.co.nz>

Icom (UK) Ltd.

Unit 9, Sea St., Herne Bay,
Kent, CT6 8LD, U.K.
Phone : +44 (0)1227 741741
Fax : +44 (0)1227 741742
E-mail : info@icomuk.co.uk
URL : <http://www.icomuk.co.uk>

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road,
Taipei, Taiwan, R.O.C.
Phone : +886 (02) 2559 1899
Fax : +886 (02) 2559 1874
E-mail : sales@asia-icom.com
URL : <http://www.asia-icom.com>

Your local distributor/dealer:

Icom Canada

Glenwood Centre #150-6165 Highway 17,
Delta, B.C., V4K 5B8, Canada
Phone : +1 (604) 954-4266
Fax : +1 (604) 952-0090
E-mail : info@icomcanada.com
URL : <http://www.icomcanada.com>

Icom (Europe) GmbH

Communication Equipment
Himmelgeister Str. 100,
D-40225 Düsseldorf, Germany
Phone : +49 (0)211 346047
Fax : +49 (0)211 333639
E-mail : info@icomeurope.com
URL : <http://www.icomeurope.com>

Icom France s.a.s.

Zac de la Plaine,
1 Rue Brindejone des Moulinais, BP 45804,
31505 Toulouse Cedex 5, France
Phone : +33 (5) 61 36 03 03
Fax : +33 (5) 61 36 03 00
E-mail : icom@icom-france.com
URL : <http://www.icom-france.com>

Beijing Icom Ltd.

10C07, Long Silver Mansion, No.88, Yong Ding
Road, Haidian District, Beijing, 100039, China
Phone : +86 (010) 5889 5391/5392/5393
Fax : +86 (010) 5889 5395
E-mail : bjicom@bjicom.com
URL : <http://www.bjicom.com>

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Road,
Clayton, VIC 3168 Australia
Phone : +61 (03) 9549 7500
Fax : +61 (03) 9549 7505
E-mail : sales@icom.net.au
URL : <http://www.icom.net.au>

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer"
08190, Sant Cugat del Valles, Barcelona, Spain
Phone : +34 (93) 590 26 70
Fax : +34 (93) 589 04 46
E-mail : icom@icomspain.com
URL : <http://www.icomspain.com>

Icom Polska

Sopot, 3 maja 54, Poland
Phone : +48 (58) 550 7135
Fax : +48 (58) 551 0484
E-mail : icompolkska@icompolkska.com.pl
URL : <http://www.icompolkska.com.pl>