




IC-F3161DT
(IDAS digital VHF transceiver with 10-keypad)
IC-F3161T
(VHF transceiver with 10-keypad)
IC-F3161DS

(IDAS digital VHF transceiver without 10-keypad IC-F3161S
(VHF transceiver without 10-keypad)

IC-F4161DT
(IDAS digital UHF transceiver with 10-keypad)
IC-F4161T
(UHF transceiver with 10-keypad)
IC-F4161DS
(IDAS digital UHF transceiver without 10-keypad)
IC-F4161S
(UHF transceiver without 10-keypad)



INTRINSICALLY SAFE VERSION











ICOM DIGITAL ADVANCED SYSTEM

Conventional/IDAS™ Digital*/IDAS™ Trunki Multi-Mode Land Mobile!



▲ IC-F3161DT/T

▲ IC-F4161DS/S

VHF TRANSCEIVERS

IC-F3161DT/T

IDAS digital/analog FM with 10-keypad

IC-F3161DS/S

IDAS digital/analog FM without 10-keypad

UHF TRANSCEIVERS

IC-F4161DT/T

IDAS digital/analog FM with 10-keypad

IC-F4161DS/S

IDAS digital/analog FM without 10-keypad

IP55 dust-protection and water jet resistance

The IC-F3161/D series meets IP55 requirements for dust-protection and water jet resistance. Its durable construction is backed up by the aluminum die-cast chassis and polycarbonate casing, allowing reliable operation under harsh weather and environmental conditions.

Lithium-Ion battery pack

The supplied 2000mAh (typ.) Li-lon battery pack, BP-232FM, provides 14 hours* of operating time.

* Typical operation Tx:Rx:Stand-by=5:5:90, power save on

Most popular signalings built-in

The 2-Tone, 5-Tone, CTCSS, DTCS and MDC signaling capabilities are built-in for group communication or selective calling. The radio can decode ten 2-Tone codes or eight 5-Tone codes on a channel. When a matched tone is received, the following actions are programmable for each code.

- Beep sound
- Bell icon
- Answer back call
- Auto TX
- Radio stun/kill/revive
- Scan

Basic LTR™/conventional mode operation

Both LTR™ trunking and conventional channels are programmable on a radio. Group, selective (DTMF), and phone call are available in LTR™ mode.

MDC 1200 Compatible

The following selective calling and ANI features are available with the built-in MDC signaling.

- PTT ID SelCall
- Radio check
- Radio stun/revive
- 500 Aliases
- Status message/request Call alert
- Emergency, emergency mic monitoring

Voting mode scanning

The voting mode scanning detects the signal strength level of repeater stations and automatically selects the strongest station, useful for roaming between 2 or more repeater sites. Once you program the voting mode to a memory zone, you can easily start voting mode operation by changing the zone setting.



* IC-F3161/F4161 "D" versions only.

Full dot-matrix LCD

Using a large full dot-matrix LCD (32 x 18 mm), the IC-F3161/D series shows upper and lower case characters clearly. The display setting is selectable from 1 line, 12 characters or 2 lines 24 characters via programming. The bottom row shows assigned functions to the [P0] to [P3] buttons.



Enhanced audio

The IC-F3161/D series employs a BTL amplifier that increases the audio output and the built-in audio compander provides clear, low noise communications.

Lone worker function

When the radio is not operated for a preset period, a beep sounds and a button push is required. If no button is pushed within that preset time, an emergency signal automatically transmits and alerts your coworker or dispatcher to any potential trouble.

Intrinsically safe

The Intrinsically safe version is approved by the FM Approvals. It is suitable for use in hazardous areas where flammable gasses or liquids are used.

See specification page for applied classes.

Other features

- 512 memory channel with 128 zones
- 8 DTMF autodial memories
- Built-in inversion type voice scrambler
- 2 step reduced power setting
- · Busy, repeater lockout functions
- · Escalating alarm
- Mode dependent scan
- · Surveillance function temporarily turns off the LED backlight and beep sound
- Powerful 5W output both in VHF and UHF
- Flash CPU for future upgrade and more...

OPTIONS

Some options may not be available in some countries. Please ask your dealer for details.



Battery pack	Туре	Voltage	Capacity	Battery life*
BP-232FM	Li-lon	7.4V	2000mAh (typ.) 1900mAh (min.)	14 hours

* Operating time is approximate time (at 20°C). 5:5:90 duty cycle with

Do not charge the BP-232FM in an explosive atmosphere.



BC-171 DESKTOP CHARGER + BC-147SA AC ADAPTER Charging time: 10 hours (approx.).



BC-160 DESKTOP CHARGER + BC-123SA AC ADAPTER Charging time: 3 hours (approx.).



BC-119N DESKTOP CHARGER + AD-106 CHARGER ADAPTER BC-145SA AC ADAPTER Charging time: 3 hours (approx.).



BC-197 MULTI-CHARGER + BC-157S AC ADAPTER Rapidly charges up to 6 battery packs. Charging time: 3 hours


BC-121N + AD-106 + BC-157S is also available.



OPC-656: For use with the BC-197 or BC-121N. (12-20V DC required).



HM-169IS: Speaker-microphone. Equivalent to IP57



HS-95: Behind-the-head headset with flexible boom microphone. **HS-97**: Throat microphone fits around your neck and picks up speech vibration. VS-1SC: PTT/VOX case. Required when using these headsets.

BELT CLIPS MB-94

MB-93: Swivel type. Prevents accidental dropping from your belt. MB-94: Alligator type. Same as supplied.



MB-96N: Swivel type belt hanger. MB-96F: Fixed type belt hanger. For use with MB-94

ANTENNAS

• FA-SC25V: 136-150MHz • FA-SC55V: 150-174MHz • FA-SC25U: 400-430MHz • FA-SC57U: 430-470MHz • FA-SC72U: 470-520MHz **CUT ANTENNAS**

• FA-SC61VC: 136-174MHz • FA-SC61UC: 380-520MHz Cut the antenna element to tune to a specific center frequency.

IDAS™ digital mode ready*



IDAS (Icom Digital Advanced System) is Icom's digital land mobile radio system using the NXDN™ common air interface. The IC-F3161D series is compatible with IDAS conventional and Type-D single-site/multi-site trunking.

* The IC-F3161DT/DS, F4161DT/DS "D" versions only. See the IDAS brochure for details.

SPECIFICATIONS

GENERAL

Frequency range

IC-F3161T/S, DT/DS 136-174MHz IC-F4161T/S, DT/DS 400-470MHz.

450-512MHz

 Number of channels : 512 channels/128 zones • Channel spacing : 12.5kHz/25kHz. 15kHz/30kHz.

6.25kHz ("D" version only)

: 16K0F3E, • Type of emission Wide

Narrow

11K0F3E, 11K0F7E, 11K0F7D 8K50F3E, 8K10F1E, 8K10F1D

Digital ("D" version only) 4K00F1E, 4K00F1D

 Antenna impedance : 50Ω

• Usable temperature range: -20°C to +40°C; -4°F to +104°F

• Power supply requirement: 7.2V DC • Current drain (at 7.2V DC; approx.):

> Transmit VHF/UHF 1.5A/1.8A (at 5W/5W)

Receive Stand-by 100mA

> 150mA/140mA (VHF/UHF) ("D" version)

rated output 600mA

 Dimensions (with BP-232FM): 53 (W) ×136 (H) ×38.5 (D) mm; (projections are not included) 2.09 (W) ×5.35 (H)×1.52 (D) in Weight (approx.) : 340a: 12.0oz (with BP-232FM)

TRANSMITTER

Output power VHF/UHF: 5W/2W/1W (Hi/L2/L1)

• Max. frequency deviation: ±5kHz (Wide), ±2.5kHz (Narrow)

 Frequency stability : ±1.0ppm · Spurious emissions : 75dB typ.

• FM Hum and Noise : 46dB typ. (Wide), 40dB typ. (Narrow) • Audio harmonic distortion: 3% typ. (AF 1kHz, 40% deviation) Modulation limiting : 60-100% of max. deviation

 FSK error : 5% Max. (Digital)

• Ext. microphone connector : 9-pin multi connector/ 2.2kΩ

Supplied accessories:

- Battery pack, BP-232FM
- Belt clip, MB-94
- Antenna (differs depending on version)

Measurements made in accordance with EIA-152C/204D, TIA-603 for analog. All stated specifications are subject to change without notice or obligation.

RECEIVER

 Sensitivity FM (W, N) : 0.25µV typ. (at 12dB SINAD)

> Digital : 0.20µV typ. (at 5% BER, "D" version only)

Adjacent channel selectivity: 75dB typ. (Wide), 68dB typ. (Narrow)

: 70dB min. Spurious response Intermodulation : 74dB typ.

 Hum and noise ratio : 46dB typ. (Wide), 40dB typ. (Narrow)

 Audio output power : 500mW typ.

(at 5% distortion with an 8Ω load)

External speaker connector: 9-pin multi connector/ 8Ω

Applicable U.S. Military Specifications & IP Rating

Icom makes rugged products that have been tested to and passed the following MIL-STD requirements and Ingress Protection standards.

Standard	MIL 810F		
Standard	Method	Procedure	
Low Pressure	500.4	I, II	
High Temperature	501.4	I, II	
Low Temperature	502.4	I, II	
Temperature Shock	503.4	I	
Solar Radiation	505.4	I	
Rain Blowing/Drip	506.4	I, III	
Humidity	507.4	_	
Salt Fog	509.4	_	
Dust Blowing	510.4	I	
Vibration	514.5	I	
Shock	516.5	I, IV	

Also meets equivalent MIL-STD-810-C, -D and -E

Ingress Protection Standard	
Dust & Water	IP55 (Dust-protection and water jet resistance)
Dust & Water	IP55 (Dust-protection and water jet resistance)

INTRINSICALLY SAFE



IC-F3161T/S, IC-F4161T/S IS: Class I, II, III/ Div 1/ Groups CDEFG/ T3C Ta = 40°C

NI: Class I/ Div 2/ Groups ABCD/ T3C Ta = 40°C IC-F3161DT/DS, IC-F4161DT/DS ("D" version) (UT-126FM IDAS digital unit hardware installed)

IS: Class I, II, III/ Div 1/ Groups DEFG/ T3C Ta = 40°C NI: Class I/ Div 2/ Groups ABCD/ T3C Ta = 40°C

Special condition for use

Must be used with the BP-232FM battery.

www.icom.co.ip/world

The HM-169IS, VS-1SC, HS-94, HS-95 and HS-97 are approved as intrinsically safe options. Any other options, except the antenna, belt clip and belt hanger, cannot be used in explosive atmosphere areas.

Never charge the BP-232FM (with/without the transceiver) in an explosive atmosphere. The optional battery chargers are not approved as intrinsically safe.

lcom, Icom Inc. and Icom logo are registered trademarks of Icom Incorporated (Japan) in Japan, the United States, the United Kingdom, Germany, France, Spain, Russia, Australia, New Zealand and/or other countries. IDAS and IDAS logo are trademarks of Icom Incorporated. NXDN is a trademark of Icom Incorporated and Kenwood Corporation. LTR is a trademark of E.F. Johnson Technologies Inc. All other trademarks are the properties of their respective holders.

ICOM Inc. 1-1-32, Kami-minami, Hirano-Ku, Osaka 547-0003, Japan Phone: +81 (06) 6793 5302 Fax: +81 (06) 6793 0013 Icom America Inc.

12421 Willows Road NE. Kirkland, WA 98034, U.S.A Phone: +1 (425) 454-8155 Fax: +1 (425) 454-1509 E-mail: sales@icomamerica.com URL: http://www.icomamerica.com

Icom Canada

Glenwood Centre #150-6165 Highway 17A, Delita, B.C., V4K 5B8, Canada Phone: +1 (604) 952-4266 Fax: +1 (604) 952-0090 E-mail: info@icomcanada.com URL: http://www.icomcanada.com

Icom Brazil

Rua Itororó, 444 Padre Eustáquio Belo Horizonte MG, CEP: 30720-450, Brazil Phone: +55 (31) 3582 8847 Fax: +55 (31) 3582 8987 E-mail: sales@icombrazil.com

Icom (Europe) GmbH

Communication Equipment Auf der Krautweide 24 65812 Bad Soden am Taunus, Germany Phone: +49 (6196) 76685-0
Fax: +49 (6196) 76685-50
E-mail: info@icomeurope.com
URL: http://www.icomeurope.com

Icom Spain S.L.

Ctra. Rubi, No. 88 "Edificio Can Castanyer Bajos A 08174, Sant Cugat del Valles, Bajos A 08174, Sant Cugat del Val Barcelona, Spain Phone: +34 (93) 590 26 70 Fax: +34 (93) 589 04 46 E-mail: icom@icomspain.com URL: http://www.icomspain.com

Icom (UK) Ltd.

Blacksole House, Altira Park, Herne Bay, Kent, CT6 6GZ, U.K. Phone: +44 (0) 1227 741741 Fax: +44 (0) 1227 741742 E-mail: info@icomuk.co.uk URL: http://www.icomuk.co.uk

Icom France s.a.s.

Zac de la Plaine, 1 Rue Brindejonc des Moulinais, BP 45804. 31505 Toulouse Cedex 5, France Phone: +33 (5) 61 36 03 03 Fax: +33 (5) 61 36 03 00 mail: icom@icom-france.com RL: http://www.icom-france.com

Icom (Australia) Pty. Ltd.

Unit 1 / 103 Garden Boad. Clayton, VIC 3168 Australia Phone: +61 (03) 9549 7500 Fax: +61 (03) 9549 7505 mail: sales@icom.net.au URL: http://www.icom.net.au

Icom New Zealand

39C Rennie Drive, Airport Oaks, Auckland, New Zealand Phone: +64 (09) 274 4062 Fax: +64 (09) 274 4708 E-mail: inquiries@icom.co.nz URL: http://www.icom.co.nz

Asia Icom Inc.

6F No. 68, Sec. 1 Cheng-Teh Road Taipei, Taiwan, R.O.C. Phone: +886 (02) 2559 1899 Fax: +886 (02) 2559 1874 E-mail: sales@asia-icom.com http://www.asia-icom.com

Shanghai Icom Ltd.

No. 101, Building 9, Caifuxingyuan Park, No. 188 Maoting Road, Chedun Town, Songjiang District, Shanghai, 201611, China Phone: +86 (021) 6153 2768 Fax: +86 (021) 5765 9987 E-mall: bjicom@bjicom.com URL: http://www.bjicom.com

Your local distributor/dealer:

Count on us!